

# SERVO MOTOR TYPE VOLTAGE STABILIZER

DESK TYPE SINGLE PHASE AUTOMATIC VOLTAGE REGULATOR

SVC 卧式单相高精度全自动交流稳压器



**JOHSUN** TEC<sup>®</sup>

## Performance

Single-phase input voltage	160V-250V/100V-260V	Frequency	50Hz/60Hz
Single-phase output voltage	0.5KVA-3KVA 220V and 110V 5KVA-30KVA 220V	Adjustable time	<1s( when input voltage has a change of 10%)
		Ambient temperature	-5°C~+40°C
		Waveform distortion	No additional waveform distortion
		Load power factor	0.8
		Dielectric strength	1500V/1min
Accuracy of voltage stabilization	220V±3% 110V±6%	Insulation resistance	≥2MΩ

## Model and spec

Spec(KVA)	Product size D×W×H(cm)	Package size D×W×H(cm)	Qty	Input Range	Item Code	Input Range	Item Code
Single-phase two-wire (desk type)	SVC-0.5	17×19×13	4	160-250V	JA0101	100-260V	JA0109
	SVC-1	20×22×16	4	160-250V	JA0102	100-260V	JA0110
	SVC-1.5	20×22×16	4	160-250V	JA0103	100-260V	JA0111
	SVC-2	26×24×19	2	160-250V	JA0104	100-260V	JA0112
	SVC-3	29×22×24	2	160-250V	JA0105	100-260V	JA0113
	SVC-5	46×24×19	1	160-250V	JA0106	100-260V	JA0114
	SVC-8	57×27×24	1	160-250V	JA0107	100-260V	JA0115
	SVC-10	57×27×24	1	160-250V	JA0108	100-260V	JA0116



OVER VOLTAGE PROTECTION



DELAY TIME



LOW VOLTAGE PROTECTION



OVER TEMP PROTECTION

